

I claim:

1. An easel, comprising:
  - a first vertical support member including a first interior and a first pulley  
5 assembly positioned in said first interior;
  - a second vertical support member including a second interior and a second pulley assembly positioned in said second interior;
  - a first horizontal support member secured directly to and extending between  
said first vertical support member and said second vertical support member and  
10 adapted to secure a first edge of an artist work piece thereto; and
  - a second horizontal support member secured directly to and extending  
between said first vertical support member and said second vertical support member  
and adapted to secure a second edge of an artist work piece thereto,
  - wherein said first horizontal support member is moved vertically on said first  
15 vertical support member by said first pulley assembly and is moved vertically on  
said second vertical support member by said second pulley assembly, and wherein  
said first horizontal support member is moved independently of said second  
horizontal support member.
2. An easel according to claim 1 wherein said first vertical support  
20 member includes a first vertical groove and wherein said first horizontal support  
member extends through said first vertical groove, and wherein said second vertical  
support member includes a second vertical groove and wherein said first horizontal  
support member extends through said second vertical groove.
3. An easel according to claim 2 wherein said first horizontal support  
25 member includes a first end region having a first vertical stabilizer plate secured  
thereto and a second end region having a second vertical stabilizer plate secured  
thereto, said first vertical stabilizer plate positioned adjacent said first vertical  
groove and said second vertical stabilizer plate positioned adjacent said second  
vertical groove.
- 30 4. An easel according to claim 3 further comprising a first brake clamp  
that surrounds said first vertical support member and said first stabilizer plate and a

second brake clamp that surrounds said second vertical support member and said second stabilizer plate.

5           5.       An easel according to claim 2 wherein said first interior includes a pulley weight track, a wheel track, and a horizontal support member track positioned adjacent said first vertical groove and wherein said second interior includes a pulley weight track, a wheel track, and a horizontal support member track positioned adjacent said second vertical groove.

10           6.       An easel according to claim 1 wherein said first pulley assembly includes first and second wheels positioned on opposite sides of said first horizontal support member, and an axle extending through said first and second wheels and said first horizontal support member.

15           7.       An easel according to claim 1 further comprising a third pulley assembly positioned in said first interior and a fourth pulley assembly positioned in said second interior, wherein said second horizontal support member is moved vertically on said first vertical support member by said third pulley assembly and is moved vertically on said second vertical support member by said fourth pulley assembly, and wherein said second horizontal support member is moved independently of said first horizontal support member.

20           8.       An easel according to claim 7 wherein said first pulley assembly is positioned in a top region of said first vertical support member, said second pulley assembly is positioned in a top region of said second vertical support member, said third pulley assembly is positioned in a central region of said first vertical support member, and said fourth pulley assembly is positioned in a central region of said second vertical support member.

25           9.       An easel according to claim 1 further comprising a rail sleeve slidably mounted on said first horizontal support member, said rail sleeve securing a first edge of an artist work piece from rearward movement relative to said first horizontal support member.

30           10.      An easel according to claim 9 further comprising a rail sleeve insert secured on said rail sleeve, said rail sleeve insert securing said first edge of said artist work piece from lateral movement along said first horizontal support member.

11. An easel according to claim 1 further comprising a ceiling bracket secured to a top region of said first vertical support member and a floor bracket secured to a bottom region of said first vertical support member.
12. An easel for supporting an artist work piece, comprising:
- 5 a vertical support member including an interior;  
a pulley system positioned completely within said interior, said pulley system adapted for moving a horizontal support member on said vertical support member; and  
a horizontal support member secured to said pulley system and extending  
10 into said interior of said vertical support member.
13. An easel according to claim 12 wherein said interior includes a pulley weight track, a wheel track and a vertical support member track.
14. An easel according to claim 13 wherein said pulley system comprises:
- 15 a pulley weight slidably positioned within said pulley weight track;  
a wheel movably positioned within said wheel track;  
a wheel axle extending through said wheel and an end region of said vertical support member positioned within said vertical support member track;  
a pulley roller; and  
20 a pulley cable secured in a first end region to said pulley weight and in a second end region to said wheel axle, and extending over said pulley roller.
15. An easel according to claim 12 further comprising a stabilizer plate positioned against said vertical support member and having an aperture, said horizontal support member extending through said aperture and into said interior of  
25 said vertical support member.
16. An easel according to claim 15 further comprising:
- a brake bracket movably mounted on said vertical support member and horizontally surrounding said vertical support member and said stabilizer plate; and  
a tightening member secured within said brake bracket and adapted for  
30 stationarily securing said stabilizer plate on vertical support member.

17. An easel according to claim 15 further comprising a brake block secured to said stabilizer plate and positioned within said vertical support member interior.

18. A support structure for an artist work piece, comprising:  
5 vertical support means for supporting a horizontal support means, said vertical support means including an interior;  
vertical translation means for vertically translating a horizontal support means on said vertical support means, said vertical translation means positioned within said interior; and  
10 horizontal support means for horizontally supporting an artist work piece, said horizontal support means secured to said vertical translation means.

19. A support structure according to claim 18 wherein said vertical support means comprises:  
a pulley weight track;  
15 first and second pulley wheel tracks each positioned adjacent said pulley weight track, and  
said first and second pulley wheel tracks together defining a horizontal support means track therebetween.

20. A support structure according to claim 18 further comprising a floor bracket, a ceiling bracket and a brake bracket, wherein said pulley weight track, said first and second pulley wheel tracks, and said horizontal support means track each extend through said floor bracket, said ceiling bracket and said brake bracket.

21. A artist's easel, comprising:  
a pair of vertical supports, each support including a rectangular cross section  
25 having a weight track, two pulley wheel tracks and a wheel axle track extending between said two pulley wheel tracks;

a pair of horizontal supports each including a first end extending into said wheel axle track of one of said pair of vertical supports and each including a second end extending into said wheel axle track of the other of said pair of vertical supports;  
30 first and second pulley assemblies positioned completely within an interior of one of said pair of vertical supports; and

third and fourth pulley assemblies positioned completely within an interior of the other of said pair of vertical supports,

wherein one of said horizontal supports is secured to said first and third pulley assemblies for movement along said vertical supports, and wherein the other  
5 of said horizontal supports is secured to said second and fourth pulley assemblies for movement along said vertical supports.

22. An easel according to claim 21 wherein said pair of vertical supports each define a depth, said easel defines a depth, and wherein said depth of said vertical supports is the same as the depth of said easel.

10

15

20